Galaxy Surfactants Ltd.

C-49/2, 1	TC Industrial Area, Pawne, Navi Mumbai-400 703, India.	
Tel No	: +91-22- 65134444/27616666	
Fax	: +91-22- 27615883/27615886	
Email	: galaxy@galaxysurfactants.com	
Website	: www.galaxysurfactants.com	

TECHNICAL DATA SHEET

Product Name

DESCRIPTION



Galsoft NaLS

Chemical Name	: Sarcosine, <i>N</i> -lauroyl-, sodium salt
INCI Name	: Sodium Lauroyl Sarcosinate
CAS Number	: 137-16-6
EC Number	: 205-281-5
Chemical Formula	: RCON(CH ₃)CH ₂ COONa
	$(RCO = C_{12} natural)$

TECHNICAL SPECIFICATIONS

Appearance / Nature	: Clear liquid
Odour	: Mild, characteristic
Colour	: Colourless to light pale yellow
Solids content (105°C, 2 hrs), % by mass	: 29.0 - 32.0
pH (10 % aqueous solution)	: 7.5 - 8.5
Chloride as NaCl, % by mass, maximum	: 1.0
Free fatty acid, % by mass, maximum	: 1.0
Microbial count, TVC, cfu / ml	: < 10
Microbial count, Y / M, cfu / ml	: < 10

Galsoft NaLS



TECHNICAL DATA SHEET

PROPERTIES

- Mild to skin and hair
- Excellent foaming surfactant. Gives rich, creamy lather even at high pH
- High resistance to sebum
- Tolerant to salt
- Provides silky softness and lubricity to skin
- Compatible with many cationics
- Substantive to skin and hair

APPLICATIONS

Galsoft NaLS is used in wide range of applications such as:

- Shampoos
- Mild facial cleansers
- Body washes and foam baths
- Baby products
- Liquid soaps
- Antibacterial hand washes
- Shaving preparations

PACKING

Galsoft NaLS is available in 200 litres HMHDPE carboys. Total of 80 carboys i.e. 16 MT can be shipped either palletized or non-palletized in 20 ft. full container load. It can also be supplied in IBC of 1 MT capacity. Total of 18 IBC i.e. 18 MT can be shipped in 20 ft. full container load

Galsoft NaLS

TECHNICAL DATA SHEET

HANDLING AND STORAGE

Store the material at 25 - 35°C in a clean and dry place away from direct heat and sunlight. Keep the containers tightly closed. In original sealed container, when stored as suggested, shelf life of the product is at least one year. Product solidifies if stored at \leq - 3°C. If the product becomes frozen in IBC / HMHDPE carboys, then keep the same in hot room of 30 - 40°C (avoid direct heating). Homogenize the product before use. Spills should be contained / collected and disposed off as per the regulations. Avoid ingestion, contact with eyes and prolonged contact with skin and clothing. In case of contact with eyes, seek adequate and timely medical attention, if necessary. During storage, do not stack IBC and carboys (palletized and non-palletized) one above the other

Product Name	: Galsoft NaLS
Version	: 04
Date of issue	: 15 th October, 2015
TDS Updated by	: BB / AD
Authorised by	: BP

The information contained herein is based on the data considered accurate. However, no warranty is expressed, or implied regarding the accuracy of this data or the result to be obtained from the use thereof. Galaxy assumes no responsibility for injury to the user, or third person proximately caused by the material, if reasonable safety procedures are not adhered to, as stipulated in the safety data sheet. Galaxy assumes no responsibility for injury to the user, or third person proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Further, user assumes the risk in his use of the material.